

motorsport range **CAR8949AM20**

6-piston radial mount monobloc caliper

Part numbers and handing

Rotor Thickness	Position	Ø31.8 / 34.9 / 41.3 pistons
28mm	LH trailing	CAR8949AM20SSL
	RH trailing	CAR8949AM20SSR



Replacement parts

Item	Ø31.8 / 34.9 / 41.3 pistons
Seal Kit, axle set	CSK323541E751
Pistons, STAINLESS STEEL (each)	PSS3233X600 PSS3533X600 PSS4133X600
AKB Springs (each)	SSC3435X609 (x4) SSC3435X623 (x2)
Pad abutment	PSC4489X554L PSC4489X554R PSC4489X555
Bleed screw	FSB3430X994
O seal	SER0080X841

Applications

Off-road, Trophy Truck.

Key features and benefits

- Differential piston diameters that minimise pad taper wear.
- Stainless steel pistons with wear resistant coating.
- High temperature seals.
- 2kg (4.4lbs) anti knock-back springs.
- Hard stainless steel wear plates.
- Fully optimised monobloc design for maximum stiffness.
- Internally drilled for increased protection.

Specifications

- Disc diameter range: ø360mm (14.17") max.
- Disc thickness range: 28mm (1.10") max.
- Alcon pad reference: 4489, 25mm thick, 152mm long, 54mm deep, area 156cm² per caliper.

Installation dimensions

